

The next generation in LED linear luminaires, the Protecta X's revolutionary design puts LED at the centre to provide the performance of a 4ft linear in a lightweight and slimline package. Offering a robust enclosure, excellent IP and a variety of features to make installation and maintenance effortless, the Protecta X is ideal for industrial environments. Expected useful life to 70% of the initial lumens (L70) is >200,000 hours at 25°C, with an incredible 90,000 maintenance free hours at 60°C. For a luminaire with the longest life, the highest output and market-leading efficacy, choose the **Protecta X**.



#### **Mounting Options**

Ceiling. Wall. Suspended. Pole. Handrail.

#### **Standard Specification**

Protecta X LED Linear				
Enclosure	Marine grade aluminium body with polycarbonate diffuser. Driver enclosure with epoxy powder finish (RAL 9005)			
Geartray	Aluminium			
Entry	4 x M20 cable entries - 2 at each end [3 cable entries on Emergency with battery stick]			
Termination	3 core 4mm <sup>2</sup> max conductor [4 core on Emergency] with looping one end and 16A rating through wiring			
Installation	2 x M8 mounting points located on the rear of the body			
Control Gear	Electronic Driver			
Optical Distribution	Wide beam			
Colour Temperature (CCT)	5000K (Cool White)			
Colour Rendering Index (Ra)	>70			
Maintenance	Front access panel with Torx screws			
LED Lifetime @ 60°C Ambient	L70 > 200,000hrs			
System Life @ Ambient	120,000hrs @ 25°C; 90,000hrs @ 60°C [excluding battery]			
Battery	Hot-Swappable Ni-MH (6V) battery stick - externally accessed [/EM version only]			
Emergency Duration	90 mins (25% output)			
Ingress Protection	IP66/67 to EN 60529			
Surge Protection	4kV			
Electrical Supply	110-277V AC, 50/60Hz 127-250V DC			

## **Features**

- Highly Energy Efficient >135lm/W
- Screwless mains terminals
- Multiple beam distributions available
- Front access cover for easy termination
- ♦ >90,000 maintenance free hours at 60°C
- Externally accessible battery stick for ease of maintenance





Std. Cat No.	Delivered Output	Power Consumption	Ambient °C	Weight
PRXI/02L/LE	2200 lm	16W	-40 to +60	6.8kg
PRXI/05L/LE	5200 lm	36W	-40 to +60	8.8kg
PRXI/02L/LE/EM	2200 lm	18.5W	-25 to +60	7.3kg
PRXI/05L/LE/EM	5200 lm	38.5W	-25 to +60	9.3kg

Options - Suffix to Catalogue No.						
/M25	M25 cable entries	/3H 3 hour battery duration (12.5% output)				
/LBE	Looping both sides [Non Emergency only]	/4K	4000K (Neutral White) LED Strips			
/EL	Extra live termination facility (to match emergency circuit)	/SC	Screwed connection terminal block (up to 6mm <sup>2</sup> conductors)			
/EMI	Internal battery pack [replace /EM with /EMI]	/BNI	Batteries not included [Emergency version only]			
/NST	Non Self Test [Emergency version only]	/DM	DALI Dimmable driver			
/ASL	Asymmetric along length optic	/M	Medium beam optic			
/ASW	Asymmetric along width optic [05L version only]	/BP	Nickel plated brass plugs			

### Accessories order separately

	Order Code
Pole mounting bracket assembly (38-42mm diameter poles)	SPOL4-100001
Pole mounting bracket assembly (48-52mm diameter poles)	SPOL4-100002
Pole mounting bracket assembly (58-62mm diameter poles)	SPOL4-100003
Hook type ceiling bracket assembly	SPRO4-0005
Flush mounted wall bracket assembly	SPRO4-0006
Ceiling bracket assembly	SPRO4-0002
Standard wall mounting outreach bracket (use with SPOL4-100001)	NPRO4-0008
Eyebolt mounting assembly	SPRO5-0005
Protecta 4ft adaptor bracket	SPRO5-0006







# **Dimensioned Drawings**

#### **PROTECTA X - 05L**



**PROTECTA X - 02L** 





