

CERTIFICATE OF COMPLIANCE

Certificate Number 20141113- E84941
Report Reference E84941-20011214
Issue Date 2014-November-13

Issued to: HAWKE INTERNATIONAL, DIV OF HUBBELL LTD
OXFORD ST W, ASHTON-UNDER-LYNE,
LANCASHIRE,
OL7 ONA UNITED KINGDOM

**This is to certify that
representative samples of**

MARINE SHIPBOARD CABLE SEALING FITTINGS FOR
USE IN HAZARDOUS LOCATIONS
SEE ADDENDUM PAGE FOR MODELS

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

Standard No. UL 2225, 4th Ed., Cables and Cable-Fittings
for Use in Hazardous (Classified) Locations
Standard No. CAN/CSA C22.2 No. 174-M1984 (R2008),
Cable and Cable Glands for Use in Hazardous Locations.
Wiring Products
Standard No. CAN/CSA C22.2 No. 30-M1986, Rev. 1988-
11, Explosion-Proof Enclosures for Use in Class I
Hazardous Locations

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20141113- E84941
Report Reference E84941-20011214
Issue Date 2014-November-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Class I, Groups A, B, C and D, Class II, Groups E, F and G, Class III Hazardous Locations:

Series 753, Cat. Nos. 0s, 0, 3/4" 0, 1/2" A, A, 3/4" B, B, 1" C, C, 1-1/4" C2, C2, 1-1/2" D, D, 2" E, E, 2-1/2" F and F. For use only with marine shipboard cable employing copper, bronze, aluminum or steel grounding braid. For use with Hawkeseal (Bicaseal) Activator, manufactured by Chemfix or Hawkeseal 2 EP2132/C epoxy compound, manufactured by Cedesa.



Bruce Mahrenholz, Assistant Chief Engineer, Global Inspection and Field Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

